



BEST CON- CRACK FILLER

(Construction Rapid Crack Repair)

Product Description:

Best Con-Crack Filler is a ready to use rich blend of special cement and chemicals in a single dry powder flow that needs only the edition of clean water to produce an ultra-fast setting mortar.

Use of Advantage:

Best Con-Crack Filler is easy to use, requiring only the addition of water, others beneficial properties are below:

- ❖ Instant Concrete leakage stop
- ❖ Achieve high strength
- ❖ Rapid Setting with Waterproof
- ❖ Non-Shrinking
- ❖ Rapid Strength Development
- ❖ Excellent bond strength
- ❖ Non-Toxic.
- ❖ Good Adhesive properties.
- ❖ Extended working time.
- ❖ Iron & chloride free
- ❖ Low permeability

Application Area:

Best Con-Crack Filler is a suitable for patching clearance 20 mm or more, Such as

- Stopping Leakages
- Pointing & Caulking
- Joint Sealing Concrete
- Crack repair and filler
- Patching Mortar and
- Repairing honeycombs
- Anchoring of bolts
- Seal Cavities and Gaps
- Recesses

Mixing Ratio Guide:

Best Con- Crack Filler (Powder): 4
Clean Water : 1

Mixing Instrument:

Best con-Crack Filler is easily mixed by Adding clean water mix either with a Trowel or Gloved hand.

Technical & Physical Data:

Form	Premixed Powder
Color	Light Gray
Compressive Strength (N/mm2) (ASTM C942-81)	
1 Hour	>12
1 Day	>22
7 Days	>32
28 Days	>52



BEST CON- CRACK FILLER

(Construction Rapid Crack Repair)



Instruction for use:

Surface preparation:

Concrete surface should be clean, sound and free from oil, grease, laitance and loosely adhering particles

Area to be patched should be cut with a minimum depth 20-25 mm

Safety:

Safety goggles and hand gloves must be used for personal protection while handling the product. In case of contact with eyes, wash immediately in a good current of water under low pressure at least for 15 minutes. Consult physician if irritation persists after 24 hours.

Shelf Life:

Shelf life 12 Month from manufacturing date in sealed condition, keep within the temperature of 5°C to 40°C in dry place.

Application:

After mixing timing is important because of its rapid-dry characteristics. Placement time is limited to gelling period of 20 seconds. Use hand to hold and press manually when necessary until it achieves initial set.

Packaging:

5 KG, 10 KG, 20 KG Pail



Best Con

Construction Materials Co; Ltd.
Puchong, Malaysia